






## DEF Equipment Product Catalog

**KleerBlue™**


**“Your Total DEF Storage & Dispensing Solution”**

## Mini-Bulk Storage and Dispensing Systems

Type	Model	Description
<b>Retail 400</b>		<b>Application: For retail sales, interfaces with POS systems</b>
	SBD KB-2010	<p><b>Tank:</b> 400 gallon mini-bulk tank triple wall containment system, constructed of UV protected polyethylene, electrical box, redundant heating system, Leader Pump Bluediver 1000 submersible, (1) primary tank and (2) secondary tank vents, Pneumercator TMS 1000 DEF tank gauge console &amp; probe, overfill protection, (2) aluminum composite panels for advertising</p> <p><b>Dispenser:</b> Industrial grade cabinet, powder coat finish, insulated w/ dual heat, Weights &amp; Measures Approved TCS-682 stainless steel meter, Triangle Micro Systems DEF Retail Software Electronics, pulse output, Cim-Tek 1 micron cartridge filter w/ stainless steel housing, Reelcraft hose reel w/ 15' DEF hose, excludes nozzle and swivel</p> <p><b>Dimensions: 38" width x 172" length x 68" height</b></p>
<b>Retail 1000</b> (Available Fall 2010)		<b>Application: For retail sales, interfaces with POS systems</b>
 (Rendering)	SBD KB-2020	<p><b>Tank:</b> 1000 gallon mini-bulk tank triple wall containment system, constructed of UV protected polyethylene, electrical box, redundant heating system, Leader Pump Bluediver 1000 submersible, (1) primary and (2) secondary tank vents, Pneumercator TMS 1000 DEF tank gauge console &amp; probe, overfill protection, (2) aluminum composite panels for advertising</p> <p><b>Dispenser:</b> Industrial grade cabinet, powder coat finish, insulated w/ dual heat, Weights &amp; Measures Approved TCS-682 stainless steel meter, Triangle Micro Systems DEF Retail Software Electronics, pulse output, Cim-Tek 1 micron cartridge filter w/ stainless steel housing, Reelcraft hose reel w/ 15' DEF hose, excludes nozzle and swivel</p> <p><b>Dimensions: 44" width x 172" length x 106" height</b></p>
<b>Fleet 400</b>		<b>Application: For fleet fueling without need for retail sales</b>
	SBD KB-2040	<p><b>Tank:</b> 400 gallon mini-bulk tank triple wall containment system, constructed of UV protected polyethylene, electrical box, redundant heating system, Leader Pump Bluediver 1000 submersible, (1) primary and (2) secondary tank vents, overfill protection, Pneumercator TMS 1000 DEF tank gauge console &amp; probe</p> <p><b>Dispenser:</b> Industrial grade cabinet, powder coat finish, insulated w/ dual heat, positive displacement oval gear stainless steel flow meter, Triangle Micro Systems DEF Volume Only Software Electronics, pulse output, Cim-Tek 1 micron cartridge filter w/ stainless steel housing, Reelcraft hose reel w/ 15' DEF hose, excludes nozzle and swivel. Excludes aluminum composite panels for advertising shown.</p> <p><b>Dimensions: 38" width x 172" length x 68" height</b></p>









## Mini-Bulk Storage and Dispensing Systems

Type	Model	Description
<b>Fleet 1000</b> (Available Fall 2010)		<b>Application: For fleet fueling without need for retail sales</b>
 (Rendering)	SBD KB-2050	<b>Tank:</b> 1000 gallon mini-bulk tank triple wall containment system, constructed of UV protected polyethylene, electrical box, redundant heating system, Leader Pump Bluediver 1000 submersible, (1) primary and (2) secondary tank vents, overfill protection, Pneumercator TMS 1000 DEF tank gauge console & probe  <b>Dispenser:</b> Industrial grade cabinet, powder coat finish, insulated w/ dual heat, positive displacement oval gear stainless steel flow meter, Triangle Micro Systems DEF Volume Only Software Electronics, pulse output, Cim-Tek 1 micron cartridge filter w/ stainless steel housing, Reelcraft hose reel w/ 15' DEF hose, excludes nozzle and swivel  <b>Dimensions: 44" width x 172" length x 106" height</b>
<b>Commercial 400</b>		<b>Application: Economical</b>
	SBD KB-2060	<b>Tank:</b> 400 gallon mini-bulk tank triple wall containment system, constructed of UV protected polyethylene, redundant heating system, Leader Pump Bluediver 1000 submersible, (1) primary and (2) secondary tank vents, overfill protection, Krueger Sentry Gauge LED At-A-Glance w/ ALL SS Therma Gauge  <b>Dispenser:</b> Industrial grade cabinet, powder coat finish, insulated w/ heat, Tuthill Sotera 825 Electronic Meter w/ liquid crystal re-settable display, Cim-Tek 1 micron cartridge filter w/ polypropylene housing, 12' DEF hose, polypropylene trigger nozzle
<b>Commercial 1000</b> (Available Fall 2010)		<b>Application: Economical</b>
	SBD KB-2070	<b>Tank:</b> 1000 gallon mini-bulk tank triple wall containment system, constructed of UV protected polyethylene, redundant heating system, Leader Pump Bluediver 1000 submersible, (1) primary and (2) secondary tank vents, overfill protection, Krueger Sentry Gauge LED At-A-Glance w/ ALL SS Therma Gauge  <b>Dispenser:</b> Industrial grade cabinet, powder coat finish, insulated w/ heat, Tuthill Sotera 825 Electronic Meter w/ liquid crystal re-settable display, Cim-Tek 1 micron cartridge filter w/ polypropylene housing, 12' DEF hose, polypropylene trigger nozzle



## Mini-Bulk Tank Price (Fully Equipped Tank without Dispenser for connection with Remote or 3rd Party DEF Dispenser)

Type	Model	Description
<b>Retail 400</b> 	SBD KB-3410	400 gallon mini-bulk tank triple wall containment system, constructed of UV protected polyethylene, electrical box, redundant heating system, Leader Pump Bluediver 1000 submersible, (1) primary tank and (2) secondary tank vents, Pneumercator TMS 1000 DEF tank gauge console & probe, overfill protection, (2) aluminum composite panels for advertising  <b>Dimensions: 38" width x 144" length x 62" height</b>
<b>Retail 1000</b> (Available Fall 2010)  (Rendering)	SBD KB-3820	1000 gallon mini-bulk tank triple wall containment system, constructed of UV protected polyethylene, electrical box, redundant heating system, Leader Pump Bluediver 1000 submersible, (1) primary tank and (2) secondary tank vents, Pneumercator TMS 1000 DEF tank gauge console & probe, overfill protection, (2) aluminum composite panels for advertising  <b>Dimensions: 44" width x 144" length x 106" height</b>
<b>Fleet 400</b> 	SBD KB-3440	400 gallon mini-bulk tank triple wall containment system, constructed of UV protected polyethylene, electrical box, redundant heating system, Leader Pump Bluediver 1000 submersible, (1) primary tank and (2) secondary tank vents, overfill protection, Pneumercator TMS 1000 DEF tank gauge console & probe. Excludes aluminum composite panels for advertising shown.  <b>Dimensions: 38" width x 144" length x 62" height</b>
<b>Fleet 1000</b> (Available Fall 2010)  (Rendering)	SBD KB-3850	1000 gallon mini-bulk tank triple wall containment system, constructed of UV protected polyethylene, electrical box, redundant heating system, Leader Pump Bluediver 1000 submersible, (1) primary tank and (2) secondary tank vents, overfill protection, Pneumercator TMS 1000 DEF tank gauge console & probe  <b>Dimensions: 44" width x 144" length x 106" height</b>
<b>Commercial 400</b> 	SBD KB-3460	400 gallon mini-bulk tank triple wall containment system, constructed of UV protected polyethylene, redundant heating system, Leader Pump Bluediver 1000 submersible, (1) primary and (2) secondary tank vents, overfill protection, Krueger Sentry Gauge LED At-A-Glance w/ ALL SS Therma Gauge. Excludes aluminum composite panels for advertising shown.  <b>Dimensions: 38" width x 144" length x 62" height</b>
<b>Commercial 1000</b> (Available Fall 2010)  (Rendering)	SBD KB-3870	1000 gallon mini-bulk tank triple wall containment system, constructed of UV protected polyethylene, redundant heating system, Leader Pump Bluediver 1000 submersible, (1) primary and (2) secondary tank vents, overfill protection, Krueger Sentry Gauge LED At-A-Glance w/ ALL SS Therma Gauge  <b>Dimensions: 44" width x 144" length x 106" height</b>

SBD KB-MBDT-D Rev. C: SBD KleerBlue™ DEF Storage & Dispensing Equipment USA Price List – Effective 6/21/10




All Prices in US Dollars – Prices Subject to Change – All Applicable Taxes are Excluded – FOB Factory



## Mini-Bulk Tank Price (Transition and Dispenser Sump for 3rd Party DEF Dispenser)

Type	Model	Description
	SBD KB-G-DIS	Structure for setting Gilbarco Encore DEF dispenser with a KleerBlue Mini-Bulk Tank (tank & tank equipment not included)
	SBD KB-W-DIS	Structure for setting Wayne DEF Dispenser with a KleerBlue Mini-Bulk Tank (tank & tank equipment not included)
	SBD KB-X-DIS	Structure for setting other 3rd Party DEF Dispenser with a KleerBlue Mini-Bulk Tank (tank & tank equipment not included)

## Dispensers

Type	Model	Description
<b>Retail</b>		<b>Application: For connection to 3rd party DEF Mini-Bulk storage units</b>
	SBD KB-1010	Industrial grade cabinet, power coat finish, insulated w/ dual heat, Weights & Measures Approved TCS-682 stainless steel meter, Triangle Micro Systems Retail Software Electronics, pulse output, Cim-Tek 1 micron cartridge filter w/ stainless steel housing, Reelcraft hose reel w/ 15' DEF hose
<b>Fleet</b>		<b>Application: For connection to 3rd party DEF Mini-Bulk storage units</b>
	SBD KB-1040	Industrial grade cabinet, power coat finish, insulated w/ dual heat, positive displacement oval gear stainless steel flow meter, Triangle Micro Systems Volume Only Software Electronics, pulse output, Cim-Tek 1 micron cartridge filter w/ stainless steel housing, Reelcraft hose reel w/ 15' DEF hose
<b>Commercial</b>		<b>Application: For connection to 3rd party DEF Mini-Bulk storage units</b>
	SBD KB-1060	Industrial grade cabinet, power coat finish, insulated w/ heat, Tuthill Sotera 825 Electronic Meter w/ liquid crystal re-settable display, Cim-Tek 1 micron cartridge filter w/ polypropylene housing, 12' DEF hose, polypropylene trigger nozzle



*SBD KB-MBDT-D Rev. C: SBD KleerBlue™ DEF Storage & Dispensing Equipment USA Price List – Effective 6/21/10*

*All Prices in US Dollars – Prices Subject to Change – All Applicable Taxes are Excluded – FOB Factory*





## Mini-Bulk DEF Storage & Dispensing System Options

Type	Model	Description
<p>If desired, deductions or additions of the following components to the system pricing can be made if another tank gauging equipment will be used in lieu of Pneumercator TMS 1000 DEF Tank Gauge Console &amp; Probe or Krueger Sentry Gauge or no heating is necessary given specific DEF storage and dispensing application.</p>		
	SBD D-PTMS-400	Deduct Pneumercator TMS 1000 DEF Tank Gauge Console & Probe - 400
	SBD D-PTMS-1000	Deduct Pneumercator TMS 1000 DEF Tank Gauge Console & Probe - 1000
	SBD KB-DEDKTG	Deduct Krueger Sentry Gauge LED At-A-Glance w/ALL SS Therna Gauge
	SBD KB-DEDTHT	Deduct tank heat components
	SBD KB-DEDDDH	Retail & Fleet Electronic Dispenser - Deduct dual heat & insulation components
	SBD KB-DEDDCH	Commercial Dispenser - Deduct heat & insulation components







## Drum & Tote (DT) Wallpack Pumping & Dispensing Systems

Type	Model	Description
<b>DT Wallpack Retail</b> 	SBD KB-1080	<p><b>Application: Submersible System for retail sales from drums &amp; totes or mini-bulk tanks</b></p> <p>Industrial grade cabinet, powder coat finish, Weights &amp; Measures Approved TCS-682 stainless steel meter, Triangle Micro Systems DEF Retail Software Electronics, pulse output, 12' DEF delivery hose</p>
<b>DT Wallpack Fleet</b> 	SBD KB-1085	<p><b>Application: Submersible System for non-retail sales from drums &amp; totes or mini-bulk tanks</b></p> <p>Industrial grade cabinet, powder coat finish, positive displacement oval gear stainless steel flow meter, Triangle Micro Systems DEF Volume Only Software Electronics, pulse output, 12' DEF delivery hose</p>

## Drum & Tote (DT) Wallpack Pumping & Dispensing Systems

Type	Model	Description
<b>DT Retail Wallpack Pump Cabinet</b> 	SBD KB-1088	<b>Application: Pump box for connecting to DT Wallpack Retail cabinet or to reel systems in service bays</b> Industrial grade cabinet, powder coat finish, Cim-Tek 1 micron cartridge filter w/ polypropylene housing, air eliminator, Tuthill DEF stainless steel vane pump, 8' suction, 12' transfer hose
<b>DT Fleet Wallpack Pump Cabinet</b> 	SBD KB-1090	<b>Application: Pump box for connecting to DT Wallpack Fleet cabinet or to reel systems in service bays</b> Industrial grade cabinet, powder coat finish, Cim-Tek 1 micron cartridge filter w/ polypropylene housing, Tuthill DEF stainless steel vane pump, 8' suction, 12' transfer hose
<b>Pedestal Remote Retail Dispenser</b> <i>pedestal not shown</i> 	SBD KB-1092	<b>Application: Pedestal Mounted Remote dispenser for retail sales from drums &amp; totes or mini-bulk tank equipped with submersible pump</b> Industrial grade cabinet and pedestal, powder coat finish, Weights & Measures Approved TCS-682 stainless steel meter, Triangle Micro Systems DEF Retail Software Electronics, pulse output, hose hanger, 12' DEF delivery hose
<b>Pedestal Remote Fleet Dispenser</b> <i>pedestal not shown</i> 	SBD KB-1095	<b>Application: Pedestal Mounted Remote dispenser for non-retail sales from drums, totes or mini-bulk tank equipped with submersible pump</b> Industrial grade cabinet and pedestal, powder coat finish, positive displacement oval gear stainless steel flow meter, Triangle Micro Systems DEF Volume Only Software Electronics, pulse output, hose hanger, 12' DEF delivery hose

## Electronic Dispensing Solutions for 55 Gallon Drums, 275 and 330 Gallon Totes with Closed Valve System (MicroMatic Connection)

Type	Model	Description
<b>Tuthill</b>		
		The heavy duty Tuthill stainless steel self priming rotary vane pump, available with 110-volt or 12-volt continuous duty motor, delivers 7-8 GPM. Unit can be floor, wall or tote mount. The pump and motor assembly is mounted on a base and includes a 3' suction hose with stainless steel MicroMatic DV style drum valve coupler. Also included is a Tuthill Sotera 825 Electronic Meter w/ liquid crystal re-settable display, a 12' coupled delivery hose, stainless steel automatic shut-off nozzle and swivel, nozzle holder, screw clamps and thread sealant. Maximum hose length is 30'. Available with or without meter.
	SBD T-M-SS-1	<i>Only to be used for a container with MicroMatic DV extractor fitting installed.</i> Complete 110 volt pump / meter pkg / ss auto nozzle
	SBD T-M-SS-1-3	Complete 12 volt pump / meter pkg / ss auto nozzle
	SBD T-M-SS-2	Complete 110 volt pump / less meter pkg / ss auto nozzle
	SBD T-M-SS-2-3	Complete 12 volt pump / less meter pkg / ss auto nozzle
<b>Flowserve PH6</b>		
		The medium duty Flowserve PH6 self-priming diaphragm pump, available with 110-volt or 12-volt electric motor, delivers 9-10 GPM. A stainless steel MicroMatic DV style drum valve coupler is an integral part of the pump inlet, and provides a quick connection and drybreak release of the pumping unit from the 55 gallon drum, 275 or 330 gallon tote closed system. This unit includes a Flowserve SEM-10P meter w/ liquid crystal re-settable display, 12' coupled delivery hose, stainless steel automatic shut-off nozzle and swivel, nozzle holder, screw clamps and thread sealant. Maximum hose length is 30'. Available with or without meter.
	SBD FS-M-1-110	<i>Only to be used for a container with MicroMatic DV extractor fitting installed.</i> Complete 110 volt pump / meter pkg / ss auto nozzle
	SBD FS-M-1-12	Complete 12 volt pump / meter pkg / ss auto nozzle
	SBD FS-M-2-110	Complete 110 volt pump / less meter pkg / ss auto nozzle
	SBD FS-M-2-12	Complete 12 volt pump / less meter pkg / ss auto nozzle
<b>Flowserve PH6</b>		
		The medium duty Flowserve PH6 self-priming diaphragm pump, available with 110-volt or 12-volt electric motor, suitable for floor, wall mount or tote assembly, and will produce up to 6 GPM. This unit features a MicroMatic EPV drum connector on the inlet, Flowserve SEM-10P meter w/ liquid crystal re-settable display, 5' coupled suction hose and a maximum length 12' coupled delivery hose, stainless steel automatic shut-off nozzle and swivel, nozzle holder, screw clamps and thread sealant. Available with or without meter.
	SBD FS-EP1-110	<i>Only to be used for a container with MicroMatic EPV extractor fitting installed.</i> Complete 110 volt pump / meter pkg / ss auto nozzle
	SBD FS-EP1-12	Complete 12 volt pump / meter pkg / ss auto nozzle
	SBD FS-EP2-110	Complete 110 volt pump / less meter pkg / ss auto nozzle
	SBD FS-EP2-12	Complete 12 volt pump / less meter pkg / ss auto nozzle

## Electronic & Air Dispensing Solutions for 55 Gallon Drums, 275 and 330 Gallon Totes with Open Valve Systems

Type	Model	Description
------	-------	-------------

### Finish Thompson PFM



This Finish Thompson PFM series heavy duty, indoor use self-priming submersible immersion pump features a 110-volt electronic motor with variable speed control and delivers 9-10 GPM. The pump assembly attaches to a buttress threaded drum connection and the motor has a 12' power cord. The 40" pump tube should be used with 55 gallon drum. The 48" pump tube will reach to the bottom of the 275 or 330 gallon tank. This unit includes a 12' coupled delivery hose, Flowserve SEM-10P meter w/ liquid crystal re-settable display, stainless steel automatic shut-off nozzle and swivel, nozzle holder, screw clamps and thread sealant. Maximum hose length is 30'. Available with or without meter.



- SBD FTPM-E-1-8 Complete 110 volt pump / meter pkg / ss auto nozzle w/ 48" tube
- SBD FTPM-E-1-0 Complete 110 volt pump / meter pkg / ss auto nozzle - 55 gallon drum only w/ 40" tube
- SBD FTPM-E-2-8 Complete 110 volt pump / less meter pkg / ss auto nozzle w/ 48" tube
- SBD FTPM-E-2-0 Complete 110 volt pump / less meter pkg / ss auto nozzle - 55 gallon drum only w/ 40" tube

### Finish Thompson PFM



The Finish Thompson PFM series air driven self-priming submersible immersion pump can deliver up to 6 GPM. The air motor offers versatility, as it can be powered by a stationary or a portable compressed air source, or from an auxiliary air attachment on a truck. The pump assembly will attach to a buttress threaded drum connection, and has a 48" pump tube, which will reach to the bottom of the 275 or 330 gallon tank. The 40" pump tube should be used with 55 gallon drum. The air motor will operate between 20-80 PSI and requires 10 CFM. An air regulator (not included) is required for safe and satisfactory service. The unit includes a maximum length 12' coupled delivery hose; Flowserve SEM-10P meter w/ liquid crystal re-settable display, stainless steel automatic shut-off nozzle and swivel, nozzle holder, screw clamps and thread sealant. Available with or without meter.



- SBD FTPM-A-1-8 Complete air-driven pump / meter pkg / ss auto nozzle w/ 48" tube
- SBD FTPM-A-1-0 Complete air-driven pump / meter pkg / ss auto nozzle w/ 40" tube - 55 gallon drum only
- SBD FTPM-A-2-8 Complete air-driven pump / less meter pkg / ss auto nozzle w/ 48" tube
- SBD FTPM-A-2-0 Complete air-driven pump / less meter pkg / ss auto nozzle w/ 40" tube - 55 gallon drum only

### Flowserve PH6



The medium duty indoor/outdoor Flowserve PH6 self-priming diaphragm pump, with 110-volt or 12-volt electric motor, delivers 9-10 GPM. The unit includes a telescoping suction tube with a threaded adapter, 12' coupled delivery hose, Flowserve SEM-10P meter w/ liquid crystal re-settable display, stainless steel automatic shut-off nozzle and swivel, nozzle holder, screw clamps and thread sealant. Maximum hose length is 30'. Available with or without meter.



- SBD FS-1-110 Complete 110 volt pump / meter pkg / ss auto nozzle
- SBD FS-1-12 Complete 12 volt pump / meter pkg / ss auto nozzle
- SBD FS-2-110 Complete 110 volt pump / less meter pkg / ss auto nozzle
- SBD FS-2-12 Complete 12 volt pump / less meter pkg / ss auto nozzle

## Electronic & Air Dispensing Solutions for 55 Gallon Drums, 275 and 330 Gallon Totes with Open Valve Systems

Type	Model	Description
------	-------	-------------

### Flowserve PH6



The medium duty indoor/outdoor Flowserve PH6 self-priming diaphragm pump, available with 110-volt or 12-volt electric motor, delivers 9-10 GPM. To be used with 275 or 330 gallon tote only. In this configuration, the pump and motor are mounted in a "Caddy" frame, for easy portability. The unit includes a 5' suction hose which connects to the bottom outlet of the tank, 12' coupled delivery hose, Flowserve SEM-10P meter w/ liquid crystal re-settable display, stainless steel automatic shut-off nozzle and swivel, nozzle holder, screw clamps and thread sealant. Maximum hose length is 30'. Available with or without meter.

- SBD FS-C-1-110 Complete 110 volt pump / meter pkg / ss auto nozzle
- SBD FS-C-1-12 Complete 12 volt pump / meter pkg / ss auto nozzle
- SBD FS-C-2-110 Complete 110 volt pump / less meter pkg / ss auto nozzle
- SBD FS-C-2-12 Complete 12 volt pump / less meter pkg / ss auto nozzle



### Tuthill



The heavy duty Tuthill stainless steel self-priming rotary vane pump with 110-volt or 12-volt continuous duty motor delivers up to 8 GPM. Unit can be floor, wall or tote mount. In this configuration, a telescoping suction tube is attached to a threaded adapter at the top of the tank, along with the pump. Also included is a Tuthill Sotera 825 Electronic Meter w/ liquid crystal re-settable display, 12' coupled delivery hose, pump mounting plate, stainless steel automatic shut-off nozzle, screw clamps and swivel, nozzle holder and thread sealant. Maximum hose length is 30'. Available with or without meter.

- SBD T-SS-1 Complete 110 volt pump / meter pkg / ss auto nozzle
- SBD T-SS-1-3 Complete 12 volt pump / meter pkg / ss auto nozzle
- SBD T-SS-2 Complete 110 volt pump / less meter pkg / ss auto nozzle
- SBD T-SS-2-3 Complete 12 volt pump / less meter pkg / ss auto nozzle





## Manual Dispensing Solutions for 55 Gallon Drums with Open Valve System

Type	Model	Description
------	-------	-------------

### Goat Throat



The Goat Throat polypropylene hand pump works by pressurizing the container. A few strokes of this ideal mobile chemical pump allows for smooth and safe dispensing of DEF at up to 3-4 GMP. Pump includes an external pressure relief valve, and as an added safeguard an internal pressure relief valve will automatically open if the drum pressure exceeds 8 PSI. Unit comes complete with 2" buttress thread, suction tube, 8' coupled delivery hose, polypropylene trigger nozzle and nozzle holder.

SBD GT-55-PKG Hand pump / delivery hose / poly nozzle



### Tuthill



The Tuthill polypropylene piston hand pump is an economical, light duty pump for transferring DEF out of a 55-gallon drum. The pump discharges product on the down stroke and will deliver approximately one gallon per 11 strokes. Unit comes complete with suction tube. The pump will attach to 2" FNPT.

SBD T-HP Hand Pump



## 4-Wheel Trolley for 55 Gallon Drum Handling Applications

Type	Model	Description
------	-------	-------------

### 4 Wheel Trolley



This rugged 4-wheel trolley is designed to ease handling and movement of 55 gallon DEF drums. The trolley is towable, steerable and has a parking brake. It features an adjustable mounting clamp to secure the container in place and a specially designed nozzle holder. The trolley with reel comes complete with a DEF compatible spring rewind hose reel with a 15' DEF hose assembly. Note that hand pumps are not suitable for use in conjunction with the hose reel. Pump is not included.

SBD 148-4W Trolley only, less reel for all DEF pumping units

SBD 148-4W-R Trolley with reel



## Mini-Bulk, Drum & Tote Accessories

Model	Description
SBD KB-MB-SC	KleerBlue Mini-Bulk Tank - Special Color Palette (Minimum of 18 tanks) (applies to standard stock colors only)
SBD KB-MB-GRA	KleerBlue Mini-Bulk Tank Granite Color Palette (Minimum of 40 tanks)
SBD KB-ADPANEL	KleerBlue Ad Panel (set of 2) without graphics
SBD PTMS-400	Pneumercator TMS 1000 DEF Tank Gauge, Console & Probe - 400
SBD PTMS-1000	Pneumercator TMS 1000 DEF Tank Gauge, Console & Probe - 1000
SBD PTG-DRY	Pneumercator Dry Interstitial Sensor
SBD PTG-NIC	Pneumercator Ethernet option for TMS 1000 Console
SBD PTG-MODEM	Pneumercator DIAL-UP Modem option for TMS 1000 Console
SBD KB-KSG	Krueger Sentry Tank Gauge LED AT-A-Glance
SBD OPW1672-2	OPW 1672 2" stainless steel male Kamvalok adaptor
SBD OPW1772-2	OPW 1772 2" stainless steel female coupler Kamvalok
SBD TMSCONS	Triangle Micro Systems EZ 8/16 Console System
SBD TMSPRTR	Triangle Micro Systems Printer
SBD TMSCABLE	Triangle Micro Systems 200' Cable
SBD KB-AN400-KIT	Anchor Kit for 400 Gallon Mini Bulk Tank
SBD KB-AN1000-KIT	Anchor Kit for 1000 Gallon Mini Bulk Tank
SBD POLYNOZZLE	Polypropylene 1" NPT trigger nozzle
SBD SSNOZZLE	Stainless steel automatic nozzle with swivel and 3/4" hose barb
SBD OPWSSNOZZLE	OPW 21GU-0500 stainless steel automatic nozzle with mis-filling prevention, 21GU-SSB breakaway and swivel combo, 1" BSPP female threads
SBD OPWMFPD	OPW Mis-Filling prevention Device
SBD SEM-10P	Flowserve electronic 1" pump mount meter w/ liquid crystal display
SBD SEM-10FTP	Flowserve electronic 1" hose end style meter w/ crystal display
SBD TUT-825	Tuthill electronic 1" hose end style meter w/ liquid crystal display
SBD DEFMMCDVHB	MicroMatic DV stainless steel withdraw coupler 3/4" hose barb connection
SBD DEFMMCDV	MicroMatic DV stainless steel withdraw coupler 3/4" BSPP female threads
SBD DEFMMCEPVH	MicroMatic EPV stainless steel withdraw coupler 3/4" hose barb connection
SBD DEFMMCEPV	MicroMatic EPV stainless steel withdraw coupler 1/2" BSPP male threads
SBD CDQPC	Colder "DrumQuik Pro" polypropylene coupler 3/4" hose barb connection
SBD DEFSEALANT	Liquid thread sealant for DEF 1.6 Oz. tube

*SBD KB-MBDT-D Rev. C: SBD KleerBlue™ DEF Storage & Dispensing Equipment USA Price List – Effective 6/21/10*

*All Prices in US Dollars – Prices Subject to Change – All Applicable Taxes are Excluded – FOB Factory*



## Mini-Bulk, Drum & Tote Accessories

Model	Description
SBD WRENCH	Drum and tote bung wrench
SBD POLYFILTER	Polypropylene ¾" filter with 1 micron cartridge
SBD SSFILTER	Stainless Steel 1" filter with 1 micron cartridge
SBD 1MICRON	1 micron replacement cartridges (quantity of 4 )
SBD HHANGER	Hose Hanger for totes
SBD NOZZLEHOLD	Nozzle Holder-Stainless for drum or tote
SBD REEL	ReelCraft reel spring rewind- up to 25' of hose
SBD D1X5S	5' DEF suction hose SS 1" MNPT
SBD D1X12SO	12' DEF discharge hose SS 1" MNPT one end
SBD D1X12S	12' DEF discharge hose SS 1" MNPT
SBD D3/4X12SPP	12' DEF discharge hose SS ¾" MNPT & 1" FBSPP
SBD D1X15SO	15' DEF discharge hose SS 1" MNPT one end
SBD D3/4X15SPP	15' DEF discharge hose SS ¾" MNPT & 1" FBSPP
SBD D1X20SO	20' DEF discharge hose SS 1" MNPT one end
SBD D3/4X20SPP	20' DEF discharge hose SS ¾" MNPT & 1" FBSPP
SBD D1X25SO	25' DEF discharge hose SS 1" MNPT one end
SBD D3/4X25SPP	25' DEF discharge hose SS ¾" MNPT & 1" FBSPP
SBD D1X30SO	30' DEF discharge hose SS 1" MNPT one end
SBD D3/4X30SPP	30' DEF discharge hose SS ¾" MNPT & 1" FBSPP
SBD D3/4X12	¾"x12' DEF Discharge hose no ends
SBD SENSOR	Sensor Level Sensor Ultra Sonic
SBD DEF-201KIT	Refractometer for testing the concentration of DEF. Complete with rubber protection jacket and storage case.
SBD DEF-202KIT	Refractometer for testing the concentration and refractive index of DEF. Complete with rubber protection jacket and storage case.